

Doodle

















Doodle

Doodle is definitely the eyecatcher in our Avant Garde Collection. This collection offers articles with creative, modern and trendy structures. Doodle is a perfect example for a nice decorative and creative Textaafoam original.

This knitted high-pile furniture fabric is pleasantly soft and has a very distinctive character. Doodle is piece dyed and has a woven backing that provides extra stability. This trendy and voluminous upholstery textile is suitable for all types of upholstery. We have opted for a wide and trendy colour palette. This curly fabric is also amazingly resilient.

Kindly note that during upholstering, loose fibres will come of. Due to lamination we have tried to minimize this, but this is a property of such kind of textile. It is advised to use air pressure after upholstering this Doodle quality.

A deviation of 10% in the look of the curly effect should be accepted, due to the finishing proces, humidity and (out)side temperature.

Cleaning and maintenance of Doodle is best only with a damp cloth and not too much water. Kindly let it dry completely before you use your furniture again.

Bring your furniture to life with Doodle.

- Seat depression is to be expected, this is one of the characteristics of this high-pile fabric.
- Be careful with sharp objects, Velcro or other material that could damage the fabric. Don't use brushes or other care products to remodel the curly aspect.
- Please note that washing might have a slight influence on the appearance of the article.
- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

Textaafoam originals Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

Composition

/ faceside 100%PES / backside 100%PES / knitwear





Please note: colours may vary according to your screen settings.



taupe 12

Doodle - Article passport A super soft high-pile fabric with a curly aspect. Available from stock in a wide range of contemporary and commercial colours.

Product characteristics				
Productgroup	knitwear			
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery			
Composition faceside	100%PES			
Composition backside	100%PES			
Bonding	woven			
Statistic code	6001100090			
Dyeing method	piece dyed			
Available colours	13			
Packaging	bubble wrap			•

Durability specifications									
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09	
				Dry	Wet	DGM	DGM+	1	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	>100.000		min. 20.000	min. 40.000	А	
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	n/a		min. 3-4	min. 4	n/a	
Colour fastness to light	DIN EN ISO 105-B02:2014-11. Process 3, exposure level 5								
	light colours	CTL	grade	5		min. 4	min.5	В	
	middle colours	CTL	grade	5		min. 4	min.5	В	
	dark colours	CTL	grade	5		min. 4	min.5	В	
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11								
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A	
	middle colours	CTL	grade	4-5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A	
	dark colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A	
Ignitability (cigarette test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed					

Processing specifications								
Minimum workable width in centimeters	± 143							
Roll length in meters	± 20							
Material weight in grams per linear meter	± 1020							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	612	640	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	104,6	92,5	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	1,0	1,0	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	13,8	15,3	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		pa	ssed			•
	Oeko-Tex, product class II	Centexbel		certified		1		

Cleaning specifications			•					
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	0,0	0,0	n/a	n/a	/























