



Mojo





Mojo

Mojo is where comfort meets style and is part of the Textaafoam Comfort Collection. Softness, volume and elegance are just some of the characteristics for this type of textiles.

Woven on a dobby loom, this yarn-dyed fabric delivers a unique mix of bouclé and chenille. Creating a special texture that is both trendy and timeless.

Its soft touch and fresh, fashion-forward look makes it perfectly suitable for any kind of furniture. Due to a special finish, including coating and thumbing, Mojo not only stands out in style but also has a nice and thick handfeel. Machine-washable at 30°Celsius, it's designed for easy maintenance while keeping your furniture looking sharp and on-trend.

Blending the best elements of modern fashion, Mojo adds a fresh, one-of-a-kind touch to any furniture piece. Stylish, practical, and totally in line with today's trends.

- Always be careful with sharp or rough objects such as watches, buckles or velcro, as they may damage the fabric.

- When a loop occurs, push it careful back with a blunt object.

- Please note that through daily use a certain hairiness may occur, this can easily be taken away with a pilling machine and has no further influence on the durability of this textile.

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

Textaafoam originals Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

Composition

/ faceside 46%PES 37%PAC 16%CO 1%VI
/ backside n/a
/ chenille jacquard

Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery



beige 05



brass 170



clay 84



cognac 28



darkblue 48




darkbrown 18



graphite 66



ivory 101



lightgrey 60



niagara 158



orchid 179



pesto 194

Please note: colours may vary according to your screen settings.



shitake 124



zinc 167

Please note: colours may vary according to your screen settings.

Mojo - Article passport


Mojo is an article with a soft touch and fresh, fashion-forward look.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	chenille jacquard	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	46%PES 37%PAC 16%CO 1%VI	
Composition backside	n/a	
Coating	transparent	
Statistic code	58013600	
Dyeing method	yarn dyed	
Available colours	14	
Packaging	transparent plastic	






Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	30.000		min. 12.000	min. 16.000	B
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4-5		min. 3-4	min. 4	A
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	4-5		min. 4	min.5	B-C
	middle colours	CTL	grade	4-5		min. 4	min.5	B-C
	dark colours	CTL	grade	4-5		min. 4	min.5	B-C
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	4	3-4	dry: 4, wet: 3	dry: > 4, wet: 3-4	B/A
	middle colours	CTL	grade	4	3-4	dry: 4, wet: 3	dry: > 4, wet: 3-4	B/A
	dark colours	CTL	grade	4	3-4	dry: 4, wet: 3	dry: > 4, wet: 3-4	B/A
Ignitability (cigarette test)	 BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed				

Processing specifications

Minimum workable width in centimeters	± 138							
Roll length in meters	± 35							
Material weight in grams per linear meter	± 530							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	890	460	min. 350	min. 400	A/B
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	70,0	80,0	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	3,8	3,3	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	n/a	n/a	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	2,0	2,0	n/a	n/a	A/A
    		- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.						



Textaafoam b.v.

La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934

F +31(0)13 534 7586

E info@textaafoam.nl

www.textaafoam.nl