



Avente





Avente

Avente is a luxurious upholstery textile, woven on a jacquard loom and part of our Timeless Collection. This collection features all our creative essentials. Fabrics that offer the best value for money and suit every style all year round.

Avente combines virgin and recycled yarns. This heavy, yarn-dyed blended textile has an authentic look and continues to show strong market demand. Our development team selected a carefully balanced range of commercial and natural colours. All modern tones with varying degrees of multicolour to meet every style.

The textile is finished with a light 'kiss' coating to add body and strength, without affecting the soft handfeel. Due to the rough construction of Avente, we recommend a minimum seam allowance of 1 cm. Kindly note that extra overlocking of the seam provides much more stability, especially with tightly upholstered furniture.

During use, a certain hairiness may occur. This can be removed with a pilling machine and does not affect the fabric's durability or lifecycle.

For loose-fitted upholstery models, Avente is machine-washable at 30 degrees Celsius*.

- Always be careful with sharp or rough objects such as watches, buckles, or velcro, as they may damage the fabric.
- When a loop does occur, it can be easily pushed back into the fabric with a blunt object.
- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.


Textaafom originals Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

Composition

/ faceside 42%RPP 29%PES 26%PAC 3%CO
/ backside n/a
/ jacquard

Suitable for


sofa's, beds, chairs with fitted and loose fitting upholstery



charcoal 79



grey 65



lightgrey 60




liver 10



silver 125



stone 181



taupe 12

Please note: colours may vary according to your screen settings.

Avente - Article passport

This heavy, yarn-dyed blended textile has an authentic look made from virgin and recycled yarns.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

| | | |
|----------------------|---|--|
| Productgroup | jacquard | |
| Applications | sofa's, beds, chairs with fitted and loose fitting upholstery | |
| Composition faceside | 42%RPP 29%PES 26%PAC 3%CO | |
| Composition backside | n/a | |
| Coating | sbr | |
| Statistic code | 54077200 | |
| Dyeing method | yarn dyed | |
| Available colours | 7 | |
| Packaging | transparent plastic | |

Durability specifications

| Test | Test specification | Executed by laboratory: | Unit | Testresult | | Norm RAL GZ 430/4:2019-01 | Norm DIN EN 14 465:2006-09 |
|-------------------------------------|--|-------------------------|--------|------------|-----|---------------------------|----------------------------|
| | | | | Dry | Wet | | |
| Abrasion resistance - yarn breakage | DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03 | CTL | cycles | 50.000 | | min. 16.000 | min. 25.000 |
| Pilling | DIN EN ISO 12945-2:2000-11. 2000 cycles | CTL | grade | 4-5 | | min. 3-4 | min. 4 |
| Colour fastness to light | DIN EN ISO 105-BOZ:2014-11. Process 3, exposure level 5 | | | | | | |
| | light colours | CTL | grade | 4-5 | | min. 4 | min.5 |
| | middle colours | CTL | grade | 4-5 | | min. 4 | min.5 |
| | dark colours | CTL | grade | 4-5 | | min. 4 | min.5 |
| Colour fastness to rubbing | DIN EN ISO 105-X12:2016-11 | | | | | | |
| | light colours | CTL | grade | 4 | 3-4 | dry: 4, wet: 3 | B/A |
| | middle colours | CTL | grade | 4 | 3-4 | dry: 4, wet: 3 | B/A |
| | dark colours | CTL | grade | 4 | 3-4 | dry: 4, wet: 3 | B/A |
| Ignitability (cigarette test) |  BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette | CTL | | passed | | | |

Processing specifications

| Test | Test specification | Executed by laboratory: | Unit | Testresult | | Norm RAL GZ 430/4:2019-01 | Norm DIN EN 14 465:2006-09 |
|-----------------------------|--|-------------------------|--------|------------|-------|---------------------------|----------------------------|
| | | | | Warp | Weft | | |
| Tensile strength | DIN EN ISO 13934-1:2013-08 | CTL | Newton | 1.090 | 550 | min. 350 | min. 400 |
| Tear growth resistance | DIN EN ISO 13937-3:2000-06 | CTL | Newton | 270,0 | 240,0 | min. 25 | min. 30 |
| Resistance to seam slippage | DIN EN ISO 13936-2:2004-07. Load 180 N | CTL | mm | 3,8 | 3,4 | max. 5 | max. 4 |
| Delamination | DIN 53530:1981-02 | CTL | Newton | n/a | n/a | n/a | n/a |
| Chemical substances | REACH | Centexbel | | passed | | | |

Cleaning specifications

| Test | Test specification | Executed by laboratory: | Unit | Testresult | | Norm RAL GZ 430/4:2019-01 | Norm DIN EN 14 465:2006-09 |
|---|---|-------------------------|------|------------|------|---------------------------|----------------------------|
| | | | | Warp | Weft | | |
| Dimensional change for washing 30 degrees celcius / air drying | DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08 | CTL | % | 2,0 | 2,0 | n/a | n/a |
| - We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing. | | | | | | | A/A |

