



Partner



Textaafoam
Expect what's next in furniture fabrics

| Performance



Partner

Partner is a nice luxurious upholstery textile, woven on a jacquard loom and part of our Textaafoam Performance Collection. The performance collection only consists of fabrics that meet the highest standards in durability and maintenance, making them long lasting, easy to clean and suitable for every type of upholstery.

Due to the properties of the yarns used for Partner, stains hardly have any chance and can easily be taken away with nothing more than a damp cloth. No wonder this article meets all requirements of our Easy Clean Collection; www.picobello-fabrics.com.

Partner combines virgin and recycled polyester yarns. This yarn-dyed, blended textile looks authentic and has a continuous high market demand. Our development team added several contemporary colours creating a wide range of timeless colours! All modern and with an intensity varying multicoloured aspect to meet every style.

Due to the rough construction of Partner, we recommend a minimum seam allowance of 1 cm. Kindly note that extra overlocking of the seam provides much more stability, especially with tight upholstered furniture. For loose fitted upholstery models, please know that Partner is machine- washable at 30 degrees Celsius*.

The coating of Partner exists also out of 100% polyester, which makes it at the end of the lifecycle possible to recycle, as it is a complete polyester textile.

During usage, a certain hairiness may appear, kindly note that this can be taken away with a pilling razor. This has no further influence on the durability and lifecycle of this luxurious textile.

Will this textile be your new Partner?

- Always be careful with sharp or rough objects such as watches, buckles, or velcro, as they may damage the fabric.
- When a loop does occur, it can be easily pushed back into the fabric with a blunt object.
- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

***Textaafoam originals** Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.*

Composition


/ faceside 72%PES 28%RPES
/ backside n/a
/ jacquard

Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery



anthracite 67



beige 05




brandy 127 (new colour)




caramel 16



clay 84




cognac 28 (new colour)



grey 65




herb 214




ivory 101



lightbrown 115



lightgrey 60



liver 10


Please note: colours may vary according to your screen settings.



natural 01



niagara 158




oyster 175



shitake 124




stone 181



turtle 88



wood 108



zinc 167

Please note: colours may vary according to your screen settings.

Partner - Article passport


A nice luxurious quality upholstery textile, woven on a jacquard loom.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	jacquard	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	72%PES 28%RPES	
Composition backside	n/a	
Coating	transparent	
Statistic code	55121990	
Dyeing method	yarn dyed	
Available colours	20	
Packaging	transparent plastic	






Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	100.000		min. 16.000	min. 25.000	A
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4		min. 3-4	min. 4	B
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	5		min. 4	min.5	B
	middle colours	CTL	grade	5		min. 4	min.5	B
	dark colours	CTL	grade	4-5		min. 4	min.5	B-C
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	dark colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
Ignitability (cigarette test)	 BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed				

Processing specifications

Minimum workable width in centimeters	± 140							
Roll length in meters	± 25							
Material weight in grams per linear meter	± 871							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	2.280	952	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	191,0	410,0	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	3,2	1,6	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	n/a	n/a	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	3,0	3,0	n/a	n/a	B/B
<div></div> <p>- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.</p>								



Textaafoam b.v.
La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934
F +31(0)13 534 7586
E info@textaafoam.nl
www.textaafoam.nl