



Craft





Craft

Craft is a multicoloured flatwoven quality, which is in the Textafoam Performance Collection.

This collection only consists of fabrics that meet the highest standards in durability and maintenance, making them long lasting, easy to maintain and suitable for almost every type of upholstery.

Due to an extra finish Craft passes the BS5852 cigarette (ignition source 0) & match (ignition source 1) and the EN1021 cigarette (part 1) & match (part 2).

Craft has a light woolly look & feel partially contributed by the thick needle punch coating on the backside of this article. A strong bi-colour aspect combined with the rough construction provides this article its luxurious and contemporary appearance.

Craft is a great combination with Rover, Chic and Blake – also from our Performance Collection. Durable and strong this fabric is suitable for many styles of upholstery. From loose covers to tight fitted upholstery; it works perfect!

***Textafoam originals** Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.*

Composition

/ faceside 54%PAC 46%PES
/ backside n/a
/ flatweave

Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery



brown 15 (fr)



cinnamon 94 (fr)



clay 84 (fr)




coral 95 (fr)



dolphin 180 (fr)




espresso 123 (fr)



graphite 66 (fr)



green 55 (fr)



hyacinth 159 (fr)



lightgrey 60 (fr)



mustard 06 (fr)



niagara 158 (fr)

Please note: colours may vary according to your screen settings.



zinc 167 (fr)

Please note: colours may vary according to your screen settings.

Craft - Article passport

A multicoloured quality with a woolly look and feel.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	flatweave
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery
Composition faceside	54%PAC 46%PES
Composition backside	n/a
Coating	needle punch
Statistic code	54077300
Dyeing method	yarn dyed
Available colours	13
Packaging	transparent plastic

Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	55.000		min. 12.000	min. 16.000	A
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4		min. 3-4	min. 4	B
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	5		min. 4	min.5	B
	middle colours	CTL	grade	5		min. 4	min.5	B
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
Ignitability (cigarette test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	Centexbel		passed				
	DIN EN ISO 1021-2:2014. Source: smouldering cigarette	Centexbel		passed				
	Ignitability (match test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 5 part 1 Ignition source 1: match flame equivalent	Centexbel		passed			
DIN EN ISO 1021-1:2014. Source: match flame equivalent		Centexbel		passed				






Processing specifications

Minimum workable width in centimeters	± 140
Roll length in meters	± 30
Material weight in grams per linear meter	± 700

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.377	1.014	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	204,8	151,8	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	2,4	2,8	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	n/a	n/a	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	n/a	n/a	n/a	n/a	n/a



Textaafoam
Expect what's next in furniture fabrics

Textaafoam b.v.
La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934
F +31(0)13 534 7586
E info@textaafoam.nl
www.textaafoam.nl