



Gear





Gear

The best gear you'll need is now available in our Comfort collection. A collection that consists only of soft, voluminous and elegant fabrics.

Gear is a 100% virgin polyester flatwoven upholstery fabric. The chenille yarn of which this beauty is made of, is woven in a specific way to create a rich and full loop-boucle like structure. The soft touch and dull appearance give that warm embrace we are looking for.

We have chosen for a latex coating on the back, to ensure the stability of the fabric and make it more easy to upholster. Textafoam developed this yarn dyed textile in a full colourrange, which is carefully selected in a toned down earthy palette.

In most colours you will notice a certain vivid look, which we have achieved by creating an elegant tone-in-tone colourshade between the warp and weft yarns.

Gear has a woolly, fluffy and matte look, during usage it can become a bit more hairy, but this can easily be taken away with a pilling razor. Please note that this has no further influence on the durability of this textile, as it a product related property.

This textile gives an extra dimension to your furniture and is suitable for both fitted and loose fitting upholstery. Another benefit of Gear is that it is machine-washable at 30 degrees Celsius*.

- Seat depression is to be expected, this is one of the characteristics of a chenille fabric.
- Be careful with sharp objects, velcro or other material that could damage the fabric.
- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.


***Textafoam originals** Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.*

Composition

/ faceside 100%PES
/ backside n/a
/ flatweave

Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery



anthracite 67



army 14




beige 05



brass 170



camel 09




charcoal 79



cognac 28




cream 02



grey 65



hazel 96



herb 214




ivory 101

Please note: colours may vary according to your screen settings.



liver 10




natural 01




powder 209



royalblue 47



shell 196




steel 149



taupe 12



teal 198



turtle 88



wenge 192

Please note: colours may vary according to your screen settings.

Gear - Article passport

A luxurious soft and dull chenille upholstery fabric with a boucle look.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	flatweave
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery
Composition faceside	100%PES
Composition backside	n/a
Coating	transparent
Statistic code	58013600
Dyeing method	yarn dyed
Available colours	22
Packaging	bubble wrap

Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	80.000		min. 20.000	min. 40.000	A
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4-5		min. 3-4	min. 4	A
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	5		min. 4	min.5	B
	middle colours	CTL	grade	5		min. 4	min.5	B
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	4-5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	4-5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	dark colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	light colours	CTL	grade	4-5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
Ignitability (cigarette test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed				

Processing specifications

Minimum workable width in centimeters	± 141							
Roll length in meters	± 40							
Material weight in grams per linear meter	± 572							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.663	962	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	127,9	88,1	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	2,0	2,5	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	n/a	n/a	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	0,0	0,0	n/a	n/a	A/A

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.



Textaafoam
Expect what's next in furniture fabrics

Textaafoam b.v.
La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934
F +31(0)13 534 7586
E info@textaafoam.nl
www.textaafoam.nl