



Hopper





Hopper

This light shiny and bicolour flatwoven quality is in our Textafoam Timeless Collection. The collection represents all of our creative essentials.

Woven on an air jet loom, piece dyed and finished with a SBR (transparent) coating; Hopper is strong, durable and easy-to-clean. It holds all typical properties of a cationic polyester upholstery fabric and is suitable for both fitted and loose fitting upholstery.

This article has also been treated with a damp and dirt prevented finish for optimal cleanability. Hopper is resistant to moisture and washable at 30 degrees (machine wash).

- Dirt and damp prevention treatment applied.
- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.
- Please note that during washing the damp- and dirt prevented treatment will disappear faster.


***Textafoam originals** Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.*

Composition

/ faceside 100%PES
/ backside n/a
/ flatweave

Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery



anthracite 67



azure 144



beige 05



black 61



brown 15



caramel 16



chocolate 17



coffee 81



cognac 28



copper 126



denim 153



darkgrey 68

Please note: colours may vary according to your screen settings.




eucalyptus 193



fire 139



forest 162



grey 65



hunter 156



ivory 101



khaki 51



lilac 70



liver 10



maize 22



mint 50



navy 49

Please note: colours may vary according to your screen settings.



niagara 158



olive 53



onyx 169



orange 25



petrol 56



red 35



sand 03



slate 87



stone 181



teal 198



violet 72

Please note: colours may vary according to your screen settings.

Hopper - Article passport

A light shiny and bicolour flatwoven quality which is strong and durable.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	flatweave
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery
Composition faceside	100%PES
Composition backside	n/a
Coating	sbr
Statistic code	54075300
Dyeing method	piece dyed
Available colours	35
Packaging	transparent plastic

Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	>100.000		min. 12.000	min. 16.000	A
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4-5		min. 3-4	min. 4	A
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	4-5		min. 4	min.5	B-C
	middle colours	CTL	grade	4-5		min. 4	min.5	B-C
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	dark colours	CTL	grade	5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
Ignitability (cigarette test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed				

Processing specifications

Minimum workable width in centimeters	± 145
Roll length in meters	± 40
Material weight in grams per linear meter	± 497

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	2.021	1.170	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	145,2	124,7	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	4,0	4,0	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	n/a	n/a	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	-0,4	0,0	n/a	n/a	A/A



- Dirt and damp prevention treatment applied.
 - We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.
 - Please note that during washing the damp- and dirt prevented treatment will disappear faster.



Textaafoam b.v.
 La Défense 11 | 5026 SC Tilburg
 P.O. Box 12 | 5050 AA Goirle
 The Netherlands

T +31(0)13 534 5934
 F +31(0)13 534 7586
 E info@textaafoam.nl
 www.textaafoam.nl