



Jeep





Jeep

Jeep is one of our most commercial and easy-going skin qualities in our Skins Collection. Jeep is a woven fabric, made of 100% virgin polyester microfiber. This fine woven base cloth is piece dyed and printed in a single tone-in-tone colour with a very fine skin-like design, which gives depth and liveliness to the fabric.

The surface has a matte look and soft but not too smooth touch which resembles a true skin touch sensation. The backside is laminated with a fleece backing to give extra softness and stability to the fabric. The full colour range is available on stock for you in all natural leather nuances.

It's a very easy-going textile, suitable for many styles and easy to combine with any other Textafoam quality.

Quality wise, our Jeep is tough and strong and meets all upholstery test requirements. It's even machine-washable at 30 degrees Celsius, so it's easy to maintain its best appearance.

Explore your opportunities with our Jeep.

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

***Textafoam originals** Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.*

Composition

/ faceside 100%PES
/ backside 100%PES
/ microsuede woven

Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery



anthracite 67



army 14



beige 05



caramel 16



cinnamon 94



cognac 28




desert 109



espresso 123



graphite 66



grey 65



hunter 156



lightbrown 115

Please note: colours may vary according to your screen settings.



lightgrey 60



liver 10



moss 59



shitake 124



steel 149



taupe 12



tobacco 111

Please note: colours may vary according to your screen settings.

Jeep - Article passport

Article printed in a single tone-in-tone colour with a very fine skin-like design.
Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	microsuede woven	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	100%PES	
Composition backside	100%PES	
Bonding	fleece	
Statistic code	60019200	
Dyeing method	piece dyed	
Available colours	19	
Packaging	transparent plastic	

Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	50.000		min. 8.000	min. 16.000	B
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	5		min. 3-4	min. 4	A
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	4-5		min. 4	min.5	B-C
	middle colours	CTL	grade	4-5		min. 4	min.5	B-C
	dark colours	CTL	grade	4		min. 4	min.5	C
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	dark colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
gnitability (cigarette test)	 BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed				

Processing specifications

Minimum workable width in centimeters	± 138							
Roll length in meters	± 50							
Material weight in grams per linear meter	± 445							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.059	398	min. 350	min. 400	A/C
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	79,2	31,9	min. 25	min. 30	A/B
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	2,5	2,0	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	11,5	18,5	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	0,0	0,0	n/a	n/a	A/A
 - We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.								



Textaafoam b.v.
La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934
F +31(0)13 534 7586
E info@textaafoam.nl
www.textaafoam.nl