



Riga





Riga

Our quality stripe Riga is a flatwoven quality and part of our Avantgarde Collection. A collection with creative, modern, trendy and coloured patterns & structures.

Stripes are in trend, our product development team created these boucle striped colours together with a mill who is specialized in patterns and stripes.

Yarn dyed and colours which are perfect for a stand-alone or in combination with our velvets such as Royal, Juke, Seven or Unique. It gives this special contemporary aspect.

The stripe is in the weft direction, so this means 'rail-roaded'. It can be applied widely on both fitted and loose-fitting upholstery. The height of the pattern is 195 mm.

Riga has been finished with a coating, to give it extra body and easier to upholster. Due to the more rough construction and type of yarns, we recommend a minimum seam allowance of minimum 1 cm. Another kind advice is to overlock all seams for more stability, especially with tight upholstered furniture.

Kindly note that during usage, a certain woolliness/ hairiness can appear, this is a product related property, and it can easily be taken away with a pilling machine. Note that the usage of a pilling machine has no further influence of the durability.

Riga is also machine-washable at 30 degrees Celsius*.

- Please note that because the stripe pattern is running in the weft direction, some bowing (within the acceptable margin) can occur.

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.


***Textafoam originals** Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.*

Composition

/ faceside 99%PES 1%PAC
/ backside n/a
/ jacquard

Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery



beige 05



brass 170




brown 15




burgundy 34



curry 216




darkgrey 68




liver 10



natural 01



sage 203



turtle 88

Please note: colours may vary according to your screen settings.

Riga - Article passport

A jacquard-woven fabric with a stripe pattern out of bouclé yarns.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	jacquard	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	99%PES 1%PAC	
Composition backside	n/a	
Coating	transparent	
Statistic code	54075300	
Dyeing method	yarn dyed	
Available colours	10	
Packaging	transparent plastic	

Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	>100.000		min. 16.000	min. 25.000	A
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4-5		min. 3-4	min. 4	A
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	5		min. 4	min.5	B
	middle colours	CTL	grade	5		min. 4	min.5	B
	dark colours	CTL	grade	5		min. 4	min.5	B
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	dark colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
gnitability (cigarette test)	 BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed				

Processing specifications

Minimum workable width in centimeters	± 138							
Roll length in meters	± 30							
Material weight in grams per linear meter	± 742							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.514	605	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	110,6	277,2	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	2,5	1,2	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	n/a	n/a	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	-1,2	-1,6	n/a	n/a	A/A
 - We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.								



Textaafoam b.v.

La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934

F +31(0)13 534 7586

E info@textaafoam.nl

www.textaafoam.nl