



Mosaic





Mosaic

Our quality Mosaic is a jacquard woven quality and part of our Avantgarde Collection. A collection with creative, modern, trendy and coloured patterns & structures.

This yarn dyed textile has been woven on a jacquard loom, to create this special contemporary aspect. With Mosaic you get an on trend, modern and high-low structured texture.

This trendy upholstery textile fits great to any type of furniture and is perfectly combinable with many other Textafoam originals, a nice combination can be made with articles such as Pella, Royal and Crisp.

Mosaic has a rough structure and is a typical boucle pattern (size 36x36 cm), it can be applied widely on both fitted and loose-fitting upholstery. The design is all-over and has a thick bonding/ lamination creating a strong and heavy textile, which means that it is over 1 kg per meter. Kindly note that the rolls are only +/- 20 meters.

Kindly note that during usage, a certain woolliness/ hairiness can appear, this is a product related property, and it can easily be taken away with a pilling machine. Note that the usage of a pilling machine has no further influence of the durability of Mosaic. Mosaic is also machine-washable at 30 degrees Celsius*.

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

***Textafoam originals** Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.*

Composition

/ faceside 100%PES
/ backside 100%PES
/ jacquard

Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery



beige 05



brick 128



brown 15



cognac 28



grey 65



lightgrey 60



liver 10



sage 203

Please note: colours may vary according to your screen settings.

Mosaic - Article passport

Mosaic has a rough structure and is a typical boucle pattern.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	jacquard	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	100%PES	
Composition backside	100%PES	
Bonding	pongee backing	
Statistic code	54075200	
Dyeing method	yarn dyed	
Available colours	8	
Packaging	transparent plastic	

Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	>100.000		min. 12.000	min. 16.000	A
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4-5		min. 3-4	min. 4	A
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	5		min. 4	min.5	B
	middle colours	CTL	grade	5		min. 4	min.5	B
	dark colours	CTL	grade	5		min. 4	min.5	B
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	dark colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
Ignitability (cigarette test)	 BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed				

Processing specifications

Minimum workable width in centimeters	± 138							
Roll length in meters	± 20							
Material weight in grams per linear meter	± 1150							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	2.393	2.486	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	368,8	467,1	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	1,0	0,0	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	22,9	17,7	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	0,0	-0,8	n/a	n/a	A/A
 - We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.								



Textaafoam b.v.
La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934
F +31(0)13 534 7586
E info@textaafoam.nl
www.textaafoam.nl