



Motto





Motto

This piece dyed quality is in our Natura Collection, which stands for luxury and naturel fabrics. Textafoam's Natura qualities exists of complete or partially naturel fibres.

Woven on a dobby loom, Motto is a combination of 3 different naturel type of yarns and (virgin) polyester. This light melanged upholstery fabric is dyed, washed and finished in a certain way that the dye stuff is 'pulled' out of the fabric to give it a nice, authentic, crafted and washed aspect.

During use a certain wooliness or hairiness may appear, this has no further influence on the quality or durability of this fabric. Actually it enhances its character as this is a typical property of this fabric. It can easily be taken away with a pilling razor.

Motto is perfectly suitable for both fitted and loose fitting upholstery, kindly note that a variation per dyebatch is unavoidable, so colourshades will vary, due to the special finish.

Also note that dark colours can become a bit lighter during usage. Due to naturel yans, be careful with placing the furniture in the sunlight.

- Dirt and damp prevention treatment applied.

***Textafoam originals** Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.*

Composition

/ faceside 55%PES 22%VI 11%CO 12%LI
/ backside n/a
/ flatweave

Suitable for

sofa's, beds, chairs with loose fitting
upholstery



beige 05



brown 15



charcoal 79



clay 84



cognac 28



darkblue 48



darkbrown 18



eucalyptus 193



forest 162



magnolia 160



natural 01



ocre 23

Please note: colours may vary according to your screen settings.



plumb 168



shitake 124



taupe 12



winered 39

Please note: colours may vary according to your screen settings.

Motto - Article passport

A bicolour article with a nice, authentic, crafted and washed aspect.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	flatweave	
Applications	sofa's, beds, chairs with loose fitting upholstery	
Composition faceside	55%PES 22%VI 11%CO 12%LI	
Composition backside	n/a	
Coating	transparent	
Statistic code	55151190	
Dyeing method	piece dyed	
Available colours	16	
Packaging	transparent plastic	

Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	55.000		min. 12.000	min. 16.000	A
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	3-4		min. 3-4	min. 4	C
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	4		min. 4	min.5	C
	middle colours	CTL	grade	4		min. 4	min.5	C
	dark colours	CTL	grade	4		min. 4	min.5	C
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	dark colours	CTL	grade	4	3-4	dry: 4, wet: 3	dry: > 4, wet: 3-4	B/A
gnitability (cigarette test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed				

Processing specifications

Minimum workable width in centimeters	± 140							
Roll length in meters	± 40							
Material weight in grams per linear meter	± 410							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.574	963	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	180,6	143,2	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	5,0	4,5	max. 5	max. 4	B/B
Delamination	DIN 53530:1981-02	CTL	Newton	n/a	n/a	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	n/a	n/a	n/a	n/a	n/a
 - Dirt and damp prevention treatment applied.								



Textaafoam b.v.
La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934
F +31(0)13 534 7586
E info@textaafoam.nl
www.textaafoam.nl