


Craft



Textaafoam  | Performance
creativity in fabrics



Craft

Craft is a multicoloured flatwoven quality, which is in the Textaafoam Performance Collection.

This collection only consists of fabrics that meet the highest standards in durability and maintenance, making them long lasting, easy to maintain and suitable for almost every type of upholstery.

Due to an extra finish, Craft passes the BS5852 cigarette (part 0) & match (part 1) and also the EN1021 cigarette (part 1) & match (part 2).

Craft has a light woolly look & feel partially contributed by the thick needle punch coating on the backside of this article. A strong bi-colour aspect combined with the rough construction provides this article its luxurious and contemporary appearance.

Craft is a great combination with Rover, Chic and Blake - also from our Performance Collection. Durable and strong this fabric is suitable for many styles of upholstery. From loose covers to tight fitted upholstery; it works perfect! Now available from stock.


Textaafoam ^{originals} Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

Composition


/ Faceside 54%PAC 46%PES
/ Polyester polyacrylic flatweave

Suitable for


Sofa's, beds, chairs with fitted
and loose fitting upholstery




graphite 66



zinc 167




lightgrey 60




clay 84




brown 15




espresso 123



dolphin 180



niagara 158



hyacinth 159



coral 95



cinnamon 94



mustard 06



green 55

Craft - Article passport



A multicoloured quality with a woolly look and feel.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	polyester polyacrylic flatweave	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	54%PAC 46%PES	
Statistic Code	54077300	
Coating	needle punch	
Dyeing method	yarn dyed	
Available colours	13	

Durability specifications

Test	Test Specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2016-01		Norm DIN EN 14 465:2006-09
				DRY	WET	DGM	DGM+	
Abrasion Resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	55.000		min. 12.000	min. 16.000	A
Pilling	DIN EN ISO 12945-2:2000-11, 2000 cycles	CTL	grade	4		min. 3-4	min. 4	B
Colour fastness to light	DIN EN ISO 105-B02:2014-11, Process 3, exposure level 5							
	light colours	CTL	grade	5		min. 4	min. 5	A
	middle colours	CTL	grade	5		min. 4	min. 5	A
	dark colours	CTL	grade	5		min. 4	min. 5	A
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: min 4, wet: 3-4	A/A
	middle colours	CTL	grade	5	5	dry: 4, wet: 3	dry: min 4, wet: 3-4	A/A
	dark colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: min 4, wet: 3-4	A/A
Ignitability (cigarette test)	 BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) Regulations: 1988 No. 1324, Schedule 4 part I. Ignition source 0: cigarette	Centexbel	passed					
	DIN EN ISO 1021-1:2014, Source: Smouldering cigarette	Centexbel	passed					
Ignitability (match test)	 BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) Regulations: 1988 No. 1324, Schedule 4 part I. Ignition source 1: Match flame equivalent	Centexbel	passed					
	DIN EN ISO 1021-2:2014, Source: Match flame equivalent	Centexbel	passed					

Processing specifications

Minimum workable width in centimeters	± 142							
Roll length in meters	± 40							
Material weight in grams per linear meter	± 700							
Test	Test Specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2016-01		Norm DIN EN 14 465:2006-09
				WARP	WEFT	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.377	1.014	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	204.8	151,8	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	2,4	2,8	max. 5	max. 4	A/A
Chemical substances	REACH	Centexbel		passed				

Cleaning specifications

    	   
---	---



Textaafoam
creativity in fabrics

Textaafoam b.v.
La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934
F +31(0)13 534 7586
E info@textaafoam.nl
www.textaafoam.nl