

# Parq















## Parq

The Textaafoam Skins Collection features great looking leather alternatives, quality Parq is another example of this. An upholstery fabric with an elegant leather-look and a silky and smooth touch, just like real leather.

This knitted microfiber has been dyed, printed and finished with a special foil. Together with a heavy laminated fleece backing, it gives the upholstered furniture an amazing look.

Just like leather, the surface / appearance can a bit change during use, this is depending on how the furniture is used and cared for. Scratches and sharp objects can change the aspect of the surface, like a more roughened look, this is property of these qualities and it has no further influence onthe durability of this textile.

Available from stock in a nice contemporary and commercial colour-line of 10 different colours.

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

**Textaafoam originals** Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

### Composition

/ faceside 100%PES / backside 100%PES / microsuede knitted

#### Suitable for



taupe 12

Please note: colours may vary according to your screen settings.

## Parq - Article passport

Article with an elegant leather-look and a silky and smooth touch, just like real leather.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics					
Productgroup	microsuede knitted				
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery				
Composition faceside	100%PES				
Composition backside	100%PES				
Bonding	fleece				
Statistic code	60053700				
Dyeing method	piece dyed				
Available colours	10				
Dackaging	hubble wrap				

Dura	L:II	4		:4:	001		-
Dura	DIII	ILV	SDEC	ш	Cal	.IO	HS

Test		Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry		Wet	DGM	DGM+	
Abrasion resistance - yarn breakage		DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	55.000		min. 8.000	min. 16.000	В
Pilling		DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4		min. 3-4	min. 4	В
Colour fastness to light		DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5					•		
		light colours	CTL	grade	4		min. 4	min.5	С
		middle colours	CTL	grade	3-4		min. 4	min.5	С
		dark colours	CTL	grade	3-4		min. 4	min.5	С
Colour fastness to rubbing		DIN EN ISO 105-X12:2016-11							
		light colours	CTL	grade	5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
		middle colours	CTL	grade	5 4-5		dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
		dark colours	CTL	grade	4-5	3-4	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
gnitability (cigarette test)		BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	сть		passed				

D	
Processing	specifications

Minimum workable width in centimeters	± 138	П
Roll length in meters	± 40	Π
Material weight in grams per linear meter	± 616	Г

Material weight in grams per linear meter	± 616								
Test	Test specification	Executed by laboratory:	Unit	Testi	result	Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09	
				Warp	Weft	DGM	DGM+		
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.037	570	min. 350	min. 400	A/B	
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	49,8	33,4	min. 25	min. 30	A/B	
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	1,5	1,5	max. 5	max. 4	A/A	
Delamination	DIN 53530:1981-02	CTL	Newton	13,8	17,5	n/a	n/a	n/a	
Chemical substances	REACH	Centexbel		pas	ssed				

Test	Test specification	Executed by laboratory:	Unit	Testr	esult	Norm RAL GZ	430/4:2019-01	Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	СТL	%	0,1	0,0	n/a	n/a	A/A











We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.











Textaafoam b.v. La Défense 11 | 5026 SC Tilburg P.O. Box 12 | 5050 AA Goirle The Netherlands

T+31(0)13 534 5934 F +31(0)13 534 7586 E info@textaafoam.nl www.textaafoam.nl